

SAFETY DATA SHEET

Honeywell

Burdick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Methanol P&T

MSDS Number : 000000011383

Product Use Description : Solvent

Manufacturer or supplier's details : Honeywell International Inc.
1953 South Harvey Street
Muskegon, MI 49442

For more information call : 1-800-368-0050
+1-231-726-3171
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
: **Transportation (CHEMTREC): 1-800-424-9300 or**
: **+1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : liquid, clear

Color : colourless

Odor : slight alcohol-like

Hazard Summary : Flammable. In use, may form flammable/explosive vapour-air mixture. May be fatal if swallowed. May be fatal if inhaled. May be harmful if absorbed through skin. Irritating to eyes, respiratory system and skin. May cause blindness. May cause irritation of the gastrointestinal tract. Can be absorbed through skin. Repeated exposure may cause skin dryness or cracking. This product may cause adverse reproductive effects. Possible risk of harm to the unborn child.

SAFETY DATA SHEET

Honeywell

Burttick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

Potential Health Effects

- Skin** : Irritating to skin.
Can be absorbed through skin.
May be harmful if absorbed through skin.
May cause systemic poisoning with symptoms paralleling those of inhalation.
Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.
- Eyes** : Irritating to eyes.
Causes itching, burning, redness and tearing.
May cause blindness.
- Ingestion** : Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Causes headache, drowsiness or other effects to the central nervous system.
May cause systemic poisoning with symptoms paralleling those of inhalation.
- Inhalation** : Causes respiratory tract irritation.
Causes headache, drowsiness or other effects to the central nervous system.
Inhalation of high vapour concentrations can cause CNS-depression and narcosis.
May cause blindness.
- Chronic Exposure** : Causes damage to the kidneys/ liver/ eyes/ brain/ respiratory system/ central nervous system through prolonged or repeated exposure.
Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.
This product may cause adverse reproductive effects.
Possible risk of harm to the unborn child.
- Aggravated Medical Condition** : Liver disorders
Eye disorders
Skin disorders
Neurological disorders
Kidney disorders
Do not use if pregnant.
- Target Organs** : Eyes
Skin
Respiratory system

SAFETY DATA SHEET

Honeywell

Burdick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

Central nervous system
Gastrointestinal tract

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : CH4O
Chemical nature : Substance

Chemical Name	CAS-No.	Concentration
Methanol	67-56-1	100.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Call a physician immediately. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present.

Skin contact : Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician.

Ingestion : Call a physician immediately. Do NOT induce vomiting. Immediate medical attention is required. Never give anything by mouth to an unconscious person.

Notes to physician

Treatment : Treat symptomatically.

SAFETY DATA SHEET

Honeywell

Burdick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Cool closed containers exposed to fire with water spray.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.
- Specific hazards during firefighting : Flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO₂)
Formaldehyde
- Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear personal protective equipment.
Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not swallow.
Do not breathe vapours or spray mist.
Avoid contact with skin, eyes and clothing.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Discharge into the environment must be avoided.
Do not flush into surface water or sanitary sewer system.
Do not allow run-off from fire fighting to enter drains or water

SAFETY DATA SHEET

Honeywell

Burdick&Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

courses.

Methods for cleaning up : Ventilate the area.
No sparking tools should be used.
Use explosion-proof equipment.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Wear personal protective equipment.
Use only in well-ventilated areas.
Keep container tightly closed.
Do not smoke.
Do not swallow.
Do not breathe vapours or spray mist.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion : Keep away from fire, sparks and heated surfaces.
Take precautionary measures against static discharges.
Ensure all equipment is electrically grounded before beginning transfer operations.
Use explosion-proof equipment.
Keep product and empty container away from heat and sources of ignition.
No sparking tools should be used.
No smoking.

Storage

Requirements for storage areas and containers : Store in area designed for storage of flammable liquids. Protect from physical damage.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep away from heat and sources of ignition.
Keep away from direct sunlight.
Store away from incompatible substances.
Container hazardous when empty.

SAFETY DATA SHEET

Honeywell

Burdick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.
- Engineering measures : Use with local exhaust ventilation.
Prevent vapour buildup by providing adequate ventilation during and after use.
- Eye protection : Do not wear contact lenses.
Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes
- Hand protection : Solvent-resistant gloves
Gloves must be inspected prior to use.
Replace when worn.
- Skin and body protection : Wear as appropriate:
Solvent-resistant apron
Flame retardant antistatic protective clothing.
If splashes are likely to occur, wear:
Protective suit
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
Use NIOSH approved respiratory protection.
- Hygiene measures : When using do not eat, drink or smoke.
Wash hands before breaks and immediately after handling the product.
Keep working clothes separately.
Do not swallow.
Do not breathe vapours or spray mist.
Avoid contact with skin, eyes and clothing.
This material has an established AIHA ERPG exposure limit.
The current list of ERPG exposure limits can be found at <http://www.aiha.org/insideaiha/GuidelineDevelopment/ERPG/D>

SAFETY DATA SHEET

Honeywell

Burdick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

ocuments/2011erpgweelhandbook_table-only.pdf.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Methanol	67-56-1	STEL : Short term exposure limit	328 mg/m3 (250 ppm)	10 2006	CAD AB OEL: Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)
Methanol	67-56-1	SKIN_DES : Skin designation:	Can be absorbed through the skin.	10 2006	CAD AB OEL: Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)
Methanol	67-56-1	TWA : time weighted average	262 mg/m3 (200 ppm)	10 2006	CAD AB OEL: Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)
Methanol	67-56-1	TWA : time weighted average	(200 ppm)	07 2007	CAD BC OEL: Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

SAFETY DATA SHEET



Bundick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

Methanol	67-56-1	STEL : Short term exposure limit	(250 ppm)	07 2007	CAD BC OEL: Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)
----------	---------	--	-----------	------------	--

Methanol	67-56-1	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	07 2007	CAD BC OEL: Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)
----------	---------	---	--	------------	--

Methanol	67-56-1	TWA : time weighted average	(200 ppm)	03 2011	CAD MB OEL: Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)
----------	---------	--------------------------------------	-----------	------------	--

SAFETY DATA SHEET

Honeywell

Burttick&Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

Methanol	67-56-1	STEL : Short term exposure limit	(250 ppm)	03 2011	CAD MB OEL: Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)
----------	---------	--	-----------	------------	--

Methanol	67-56-1	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	03 2011	CAD MB OEL: Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)
----------	---------	---	--	------------	--

Methanol	67-56-1	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	12 2007	CAD ON OEL: Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)
----------	---------	---	--	------------	--

Methanol	67-56-1	TWA : time weighted average	(200 ppm)	11 2010	CAD ON OEL: Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)
----------	---------	--------------------------------------	-----------	------------	--

Methanol	67-56-1	STEV : Short Term Exposure Limit (STEV):	(250 ppm)	11 2010	CAD ON OEL: Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)
----------	---------	---	-----------	------------	--

SAFETY DATA SHEET

Honeywell

Burndick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

Methanol	67-56-1	8 HR ACL : 8 hour average contamin ation limit:	(200 ppm)	05 2009	CAD SK OEL: Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)
----------	---------	---	-----------	------------	--

Methanol	67-56-1	15 MIN ACL : 15 minute average contamin ation limit:	(250 ppm)	05 2009	CAD SK OEL: Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)
----------	---------	--	-----------	------------	--

Methanol	67-56-1	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	05 2009	CAD SK OEL: Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)
----------	---------	---	--	------------	--

Methanol	67-56-1	STEL : Short term exposure limit	328 mg/m3 (250 ppm)	12 2008	OEL (QUE): Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)
----------	---------	--	------------------------	------------	--

SAFETY DATA SHEET

Honeywell

Burford & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

Methanol	67-56-1	TWA : time weighted average	262 mg/m3 (200 ppm)	12 2008	OEL (QUE) Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)
----------	---------	--------------------------------------	------------------------	------------	---

Methanol	67-56-1	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	12 2008	OEL (QUE) Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)
----------	---------	---	--	------------	---

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid, clear

Color : colourless

Odor : slight alcohol-like

pH : Note: Not applicable

Melting point/freezing point : Note: Not applicable

Boiling point/boiling range : 64.7 °C

Flash point : 52 °F (11 °C)
Method: closed cup

Evaporation rate : ca. 5
Method: Compared to Butyl acetate.

SAFETY DATA SHEET

Honeywell

Burdick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

Lower explosion limit : 6 %(V)
Upper explosion limit : 36 %(V)
Vapor pressure : 129.32 hPa
at 20 °C(68 °F)
Vapor density : 1.11 Note: (Air = 1.0)
Density : 0.792 g/cm³ at 20 °C
Water solubility : Note: completely soluble
Ignition temperature : 464 °C
Molecular weight : 32.04 g/mol

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under recommended storage conditions.
Possibility of hazardous reactions : Hazardous polymerisation does not occur.
Conditions to avoid : Heat, flames and sparks.
Keep away from direct sunlight.
Incompatible materials to avoid : Strong oxidizing agents
Aluminium
Magnesium
May attack many plastics, rubbers and coatings.
Hazardous decomposition : In case of fire hazardous decomposition products may be

SAFETY DATA SHEET

Honeywell

Burdick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

products

produced such as:
Carbon monoxide
Carbon dioxide (CO₂)
Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

- Acute oral toxicity : LD50: 5,628 mg/kg
Species: Rat
- Acute inhalation toxicity : LC50: 64000 ppm
Exposure time: 4 h
Species: Rat
- Acute dermal toxicity : LD50: 15,800 mg/kg
Species: Rabbit
- Skin irritation : Species: Rabbit
Classification: irritating
Exposure time: 24 h
- Eye irritation : Species: rabbit eye
Classification: irritating
- Repeated dose toxicity : Species: Rat
Application Route: Inhalation
Test substance: Methanol
Note: Developmental Toxicity NOAEL (maternal toxicity)
10,000 ppm NOAEL (developmental toxicity) 5,000 ppm
Skeletal and visceral malformations.
- Genotoxicity in vitro : Note: In vitro tests did not show mutagenic effects
- Genotoxicity in vivo : Note: In vivo tests did not show mutagenic effects

SAFETY DATA SHEET

Honeywell

Burndick & Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish : LC50: 29,400 mg/l
Exposure time: 96 h
Species: Fathead minnow

Toxicity to daphnia and other aquatic invertebrates : LC50: 10,000 mg/l
Exposure time: 24 h
Species: Daphnia (water flea)

Toxicity to bacteria : EC50: 43,000 mg/l
Exposure time: 5 min
Species: Photobacterium phosphoreum

: EC50: 40,000 mg/l
Exposure time: 15 min
Species: Photobacterium phosphoreum

: EC50: 39,000 mg/l
Exposure time: 25 min
Species: Photobacterium phosphoreum

Further information on ecology

Additional ecological information : Accumulation in aquatic organisms is unlikely.
The product is readily degradable in the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

SAFETY DATA SHEET

Honeywell

Burdick&Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

TDG UN/ID No. : UN 1230
Proper shipping name : METHANOL
Class : 3
Packing group : II
Hazard Labels : 3 (6.1)

IATA UN/ID No. : UN 1230
Description of the goods : METHANOL
Class : 3
Packaging group : II
Hazard Labels : 3 (6.1)
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 352
Packing instruction (passenger aircraft) : Y341

IMDG UN/ID No. : UN 1230
Description of the goods : METHANOL
Class : 3
Packaging group : II
Hazard Labels : 3 (6.1)
EmS Number : F-E, S-D
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances Control Act : On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL.

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Toxic Chemical : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET



Burdick&Jackson™

232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

Control Law (TCCL) List

- Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory
- China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory
- New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

US. EPA CERCLA Hazardous Substances (40 CFR 302) : The following component(s) of this product is/are subject to release reporting under 40 CFR 302 when release exceeds the Reportable Quantity (RQ):

Reportable quantity: 5000 lbs
: Methanol 67-56-1

WHMIS Classification : B2: Flammable liquid
D1B: Toxic Material Causing Immediate and Serious Toxic Effects
D2A: Very Toxic Material Causing Other Toxic Effects
D2B: Toxic Material Causing Other Toxic Effects
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

WHMIS Components : Methanol 67-56-1

NPRI Components : Methanol 67-56-1

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET



232-4 METHANOL P&T 4L CS4

000000011383

Version 2.1

Revision Date 03/26/2015

Print Date 03/08/2017

	HMIS III	NFPA
Health hazard	: 2*	1
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 10/31/2012

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group